

**Plum Creek MDF, Inc.**  
 265 Meadow Lake Blvd  
 Columbia Falls, MT 59912

Emergency Phone: 406-892-6200  
 Other Information: 406-892-6251  
 Revised Date: November 18, 2010  
 Website: www.plumcreek.com

## SECTION 1: IDENTITY

Common Name (used on label) (Trade Name & Synonyms)	Glacier Green™, High Density Fiberboard (HDF) CFLR, CMRS, CFLM, CCAR, CDFL only	Product Thickness	HDF ≤ 0.375 "
Chemical Name	N/A		
Formula	N/A		

## SECTION 2: HAZARDOUS INGREDIENTS

Principal Hazardous Component(s) (chemical & common name(s))	% Solid Content by Dry Weight	CAS No.
SOFT WOOD DUST (100 % PRE-CONSUMER RECYCLED WOOD FIBER)	83 - 87 %	
UREA FORMALDEHYDE RESIN*	10 – 14 %	50-00-0
* Formaldehyde content	< 0.1 %	
WAX (PARAFFIN) *	< 1 %	8002-74-2
MELAMINE * (see product specific MSDS)	>1 %	
*Wax and Melamine added to improve water resistance properties		

## SECTION 3: PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point	N/A	Specific Gravity (H <sub>2</sub> O=1)	N/A	Vapor Pressure (mm Hg)	N/A			
Percent Volatile By Volume (%)	N/A	Vapor Density (Air=1)	N/A	Evaporation Rate (_____ = 1)	N/A			
Solubility In Water	N/A	Reactivity in Water	N/A					
Appearance and Odor	LIGHT TAN COLORED SOLID PANEL..							
Flash Point	N/A	Flammable Limits in Air % by Volume	Lower N/A	Upper N/A	Extinguisher Media	Water,	Auto-Ignition Temperature	400' – 500' F
Special Fire Fighting Procedures	SATURATE BOARD WITH WATER AND MOVE TO A SECURE OUTSIDE STORAGE LOCATION. AVOID BREATHING SMOKE.							
Unusual Fire and Explosion Hazards	WOOD DUST GENERATED FROM SAWING, SANDING, MACHINING, ETC. MAY CREATE A FIRE AND EXPLOSION HAZARD. AVOID DUST ACCUMULATIONS.							

## SECTION 4: PHYSICAL HAZARDS

Stability	Unstable [ ] Stable [x]	Conditions to Avoid	PYROLYSIS MAY OCCUR. AVOID DUST ACCUMULATIONS ON HOT SURFACES.				
Incompatibility (Materials to Avoid)	STRONG OXIDIZING AGENTS, STRONG ACIDS						
Hazardous Decomposition Products	TOXIC FUMES AND GASES, INCLUDING CARBON MONOXIDE, ALDEHYDES AND ORGANIC ACIDS.						
Hazardous Polymerization	May Occur [ ] Will Not Occur [x]	Conditions to Avoid	NONE				

## SECTION 5: HEALTH HAZARDS

Signs and Symptoms of Exposure	1. Acute Overexposure	WOOD DUST MAY CAUSE EYE AND RESPIRATORY IRRITATION, NASAL DRYNESS, COUGHING, SNEEZING AND WHEEZING AS A RESULT OF INHALATION. FORMALDEHYDE MAY CAUSE TEMPORARY IRRITATION OF SKIN, EYES, OR RESPIRATORY SYSTEM.				
	2. Chronic Overexposure	WOOD DUST MAY CAUSE ALLERGIC DERMATITIS AND RESPIRATORY SENSITIZATION. PROLONGED EXPOSURE TO WOOD DUST HAS BEEN REPORTED BY SOME AGENCIES TO BE ASSOCIATED WITH NASAL CANCER. FORMALDEHYDE MAY CAUSE SENSITIZATION IN SUSCEPTIBLE INDIVIDUALS. FORMALDEHYDE IS CLASSIFIED AS A PROBABLE OR POTENTIAL CARCINOGEN.				
Medical Conditions Generally Aggravated by Exposure	RESPIRATORY CONDITIONS OR ALLERGIES, SKIN CONDITIONS					
Chemical Listed as Carcinogen or Potential Carcinogen	WOOD DUST FORMALDEHYDE	National Toxicology Program	Yes[X] No [ ]	I.A.R.C. Monographs	Yes [x] No [ ]	OSHA Yes [x] No [ ]
OSHA Permissible Exposure Limit	FORMALDEHYDE WAX (PARAFFIN) WOOD DUST	0.75 ppm 2.0 mg/m3 Total: 15 mg/m3 Respirable: 5 mg/m3		Other Exposure Limit Used	2.0 ppm STEL FORMALDEHYDE 0.5 ppm ACTION	
ACGIH Threshold Limit Value	Formaldehyde WAX (PARAFFIN) WOOD DUST	0.3 ppm 2.0 mg/m3 Total: 1mg/m3				

California Proposition 65 Warning: DRILLING, SAWING, SANDING OR MACHINING WOOD PRODUCTS GENERATES WOOD DUST, A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. AVOID INHALING WOOD DUST OR USE A DUST MASK OR OTHER SAFEGAURDS FOR PERSONAL PROTECTION.

California Proposition 65 Warning: THIS PRODUCT CONTAINS FORMALDEHYDE, A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. USE ADEQUATE VENTILATION AND AVOID INHALING VAPORS AND/OR USE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT.

**HMIS RATINGS: HEALTH: 2\* FIRE: 0 PHYSICAL HAZARD: 0**  
**SCALE: 0 = MINIMAL 1 = SLIGHT 2 = MODERATE 3 = SERIOUS 4 = SEVERE**

## SECTION 6: Emergency and First Aid Procedures

1. Inhalation	EXPOSURE TO EXCESSIVE CONCENTRATIONS OF WOOD DUST MAY CAUSE UNPLEASANT DEPOSITION IN THE NASAL PASSAGE RESULTING IN DRYNESS, COUGH AND HEADACHE. AVOID BREATHING DUST, REMOVE FROM EXPOSURE.
2. Eyes	WOOD DUST MAY MECHANICALLY IRRITATE EYES RESULTING IN REDNESS OR WATERING. FLUSH WITH CLEAN WATER TO REMOVE PARTICLES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.
3. Skin	WOOD DUST MAY ELICIT CONTACT DERMATITIS IN SOME INDIVIDUALS OR CAUSE MECHANICAL IRRITATION. IF IRRITATION OR DERMATITIS DEVELOPS, SEEK MEDICAL ATTENTION.
4. Ingestion	N/A

## SECTION 7: SPECIAL PROTECTION INFORMATION

Respiratory Protection	NIOSH APPROVED RESPIRATOR							
Ventilation	Local Exhaust	RECOMMENDED	Mechanical (General)	RECOMMENDED	Special	N/A	Other	N/A
Protective Gloves	RECOMMENDED		Eye Protection	SAFETY GLASSES AND/OR GOGGLES				
Other Protective Clothing or Equipment	PROTECTIVE OUTER LAYER MAY BE DESIRABLE IN EXTREMELY DUSTY AREAS.							

## SECTION 8: SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken in Handling and Storage	PROVIDE ADEQUATE VENTILATION.
Other Precautions	STORE IN A COOL, DRY PLACE AWAY FROM OPEN FLAME, SPARKS OR HOT SURFACES.
Steps to be Taken in Case Material is Released or Spilled	VACUUM, SWEEP, OR SHOVEL TO MIINIMIZE DUST GENERATION. PROVIDE ADEQUATE VENTILATION.
Waste Disposal Methods	DISPOSE ACCORDING TO APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. RESINS USED

**IMPORTANT**

The above information is provided in good faith and believed to be correct in accordance with 29 CFR 1910.1200. Individuals receiving this information should make their own determinations as to the suitability of this product for their purposes prior to use.