

Plum Creek AB Marine Grade Plywood

Specs	<ul style="list-style-type: none"> • Slow growth inland Douglas Fir and Western Larch yield fine-grained, smooth faces • All Group 1, Struc 1 species
Faces	<ul style="list-style-type: none"> • "A" grade faces shall be limited to a total of nine repairs in a 4'x 8' panel.
Backs, Centers & Cores	<ul style="list-style-type: none"> • All backs, centers and inner plies shall be "B" grade or better and shall be full length and full width. • Neither edge of a panel shall have any cross band gap or edge splits in excess of 1/8" wide or 4 in number. No inner ply laps are allowed.
Construction & Thickness	<p>Thickness Ply count</p> <p>1/4" 3 Ply</p> <p>3/8" 4 Ply</p> <p>1/2" 5 Ply</p> <p>5/8" 7 Ply</p> <p>3/4" 7 Ply</p> <ul style="list-style-type: none"> • Panel thickness to 1 1/2" • Solid long length to 102" • Scarfed lengths to 16' • Full thick • Tongue and groove available on 5/8" - 1 1/8"

Plum Creek AC Sanded Plywood

Specs	<ul style="list-style-type: none"> • Slow growth inland Douglas Fir and Larch yield fine-grained, smooth faces • All Group 1, Struc 1 species 										
Faces	<ul style="list-style-type: none"> • "A" grade veneer • Quality wood plugs or putty repairs, minimal use of polyurethane patch • 15 plug average assures the highest face quality • Fully sanded face 										
Backs, Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerances more stringent than APA and industry specs • One piece "C" grade or better center and back 										
Construction & Thickness	<p>Thickness Ply count</p> <table data-bbox="592 850 868 1050"> <tr> <td>1/4"</td> <td>3 Ply</td> </tr> <tr> <td>3/8"</td> <td>4 Ply</td> </tr> <tr> <td>1/2"</td> <td>5 Ply</td> </tr> <tr> <td>5/8"</td> <td>5 or 7 Ply</td> </tr> <tr> <td>3/4"</td> <td>7 Ply</td> </tr> </table> <ul style="list-style-type: none"> • Standard size 4' x 8' • Panel thickness to 1 1/2" • Solid long length to 102" • Scarfed panels to 16' • Tongue and groove available on 5/8" - 1 1/8" • Underlayment stamp available 	1/4"	3 Ply	3/8"	4 Ply	1/2"	5 Ply	5/8"	5 or 7 Ply	3/4"	7 Ply
1/4"	3 Ply										
3/8"	4 Ply										
1/2"	5 Ply										
5/8"	5 or 7 Ply										
3/4"	7 Ply										

Plum Creek BC Sanded Plywood

Specs	<ul style="list-style-type: none"> • Slow growth inland Douglas Fir and Larch yield fine-grained faces • All Group 1, Struc 1 species 										
Faces	<ul style="list-style-type: none"> • Premium "B" grade veneer • Quality wood plugs or putty repairs, minimal use of polyurethane patch • Unlimited plugs and repairs • Fully sanded face with 60 grit paper 										
Backs, Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high integrity Ultra-Core™ construction featuring composed cross bands for tight core gap tolerances far more stringent than APA and industry specs • One piece "C" grade or better center and back 										
Construction & Thickness	<p>Thickness Ply count</p> <table data-bbox="592 850 868 1050"> <tr> <td>1/4"</td> <td>3 Ply</td> </tr> <tr> <td>3/8"</td> <td>4 Ply</td> </tr> <tr> <td>1/2"</td> <td>5 Ply</td> </tr> <tr> <td>5/8"</td> <td>5 or 7 Ply</td> </tr> <tr> <td>3/4"</td> <td>7 Ply</td> </tr> </table> <ul style="list-style-type: none"> • Standard size 4' x 8' • Panel thickness to 1 1/2" • Solid long length to 102" • Scarfed panels to 16' • Tongue and groove available on 5/8" - 1 1/8" 	1/4"	3 Ply	3/8"	4 Ply	1/2"	5 Ply	5/8"	5 or 7 Ply	3/4"	7 Ply
1/4"	3 Ply										
3/8"	4 Ply										
1/2"	5 Ply										
5/8"	5 or 7 Ply										
3/4"	7 Ply										

Plum Creek Douglas Fir Siding

Specs	<ul style="list-style-type: none"> • Inland western Douglas Fir known for its slow growth, fine texture and tight grain • All Group 1, Struc 1 species • Finishing characteristics well-suited for paint, heavy body or semi-transparent stain • High ply count construction ensures superior strength and stability
Faces	<ul style="list-style-type: none"> • APA "A" grade face • Quality wood plugs or putty repairs, minimal use of polyurethane patch • Average 14 plugs per panel
Backs, Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high-integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerances more stringent than APA and industry specs • One piece "C" grade center and back
Construction & Thickness	<p>Thickness Ply count</p> <p>3/8" 4 Ply No Groove</p> <p>1/2" 5 Ply No Groove, 4" OC , 8" OC</p> <p>5/8" 5 Ply No Groove, 4" OC , 8" OC, RBB</p> <ul style="list-style-type: none"> • Scarfed 9' and 10' available • Rough texture or scratch sand • Ship lap or square edge

Plum Creek Marine Deck											
Specs	<ul style="list-style-type: none"> • Designed for rigorous marine use with superior "CP" grade face • All Group 1, Struc 1 species • Available with solid core under the face • 2 side panels available 										
Faces	<ul style="list-style-type: none"> • "C" plugged grade veneer • Quality wood plugs or putty repairs, minimal use of polyurethane patch • Splits over 1/16" are filled. Sound, tight knots up to 1 1/2" • Face is touch sanded with 60 grit paper 										
Backs, Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high-integrity Ultra-Core™ construction featuring composed cross bands for tight core gap tolerances more stringent than APA and industry specs • Back is touch sanded with 60 grit paper • One piece "C" grade center and back 										
Construction & Thickness	<p>Thickness Ply count</p> <table> <tbody> <tr> <td>1/4"</td> <td>3 Ply</td> </tr> <tr> <td>3/8"</td> <td>4 Ply</td> </tr> <tr> <td>1/2"</td> <td>5 Ply</td> </tr> <tr> <td>5/8"</td> <td>5 or 7 Ply</td> </tr> <tr> <td>3/4"</td> <td>7 Ply</td> </tr> </tbody> </table> <ul style="list-style-type: none"> • Standard size 4' x 8' • Panel thickness to 1 1/2" • Solid long length to 102" • Scarfed lengths to 16' • Tongue and groove available on 5/8" - 1 1/8" • Underlayment stamp available 	1/4"	3 Ply	3/8"	4 Ply	1/2"	5 Ply	5/8"	5 or 7 Ply	3/4"	7 Ply
1/4"	3 Ply										
3/8"	4 Ply										
1/2"	5 Ply										
5/8"	5 or 7 Ply										
3/4"	7 Ply										
Preservative Treating (PTP):	Available with CCA treating to .40 minimum retention										

Plum Creek Marine Tech											
Specs	<ul style="list-style-type: none"> • Designed for rigorous marine use with superior "B" grade faces • All Group 1, Struc 1 species • Available with solid core under the face • 2 side panels available 										
Faces	<ul style="list-style-type: none"> • "B" and better face grade with no open holes or defects • Quality wood plugs or putty repairs, minimal use of polyurethane patch • Splits over 1/32" are filled. Only sound, tight pin knots allowed • Face is fully sanded with 60 grit paper 										
Backs, Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high-integrity Ultra-Core™ construction featuring composed cross-bands for tight core gap tolerances more stringent than APA and industry specs • One side panel has a high "C" grade back chosen for minimal knot holes and splits • Two side panel has a "B" plugged back - no open knot holes or defects • Back is touch sanded with 60 grit paper • One piece high "C" center and back 										
Construction & Thickness	<p>Thickness Ply count</p> <table> <tr> <td>1/4"</td> <td>3 Ply</td> </tr> <tr> <td>3/8"</td> <td>4 Ply</td> </tr> <tr> <td>1/2"</td> <td>5 Ply</td> </tr> <tr> <td>5/8"</td> <td>5 or 7 Ply</td> </tr> <tr> <td>3/4"</td> <td>7 Ply</td> </tr> </table> <ul style="list-style-type: none"> • Standard size 48" x 96" • Panel thickness to 1 1/2" • Solid long length to 102" • Scarfed lengths to 16' • Tongue and groove available on 5/8" - 1 1/8" 	1/4"	3 Ply	3/8"	4 Ply	1/2"	5 Ply	5/8"	5 or 7 Ply	3/4"	7 Ply
1/4"	3 Ply										
3/8"	4 Ply										
1/2"	5 Ply										
5/8"	5 or 7 Ply										
3/4"	7 Ply										
Preservative Treating (PTP):	Available with CCA treating to .40 minimum retention										

Plum Creek MDO Sign Grade

Specs	<ul style="list-style-type: none"> • A quality Medium Density Overlay plywood product • All Group 1, Struc 1 species • One or two step process
Faces	<ul style="list-style-type: none"> • "B" grade veneer under paper • Wood plugs or putty repairs, minimal use of polyurethane patch • Pre-primed paper available • One or two side panel available in one or two step process • Fully sanded face with two step process
Backs, Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high-integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerances more stringent than APA and industry specs • One piece "C" grade or better center and back • Primed one side panels produced with a backer sheet
Construction & Thickness	<p>Thickness Ply count</p> <p>1/4" 3 Ply</p> <p>3/8" 4 Ply</p> <p>1/2" 5 or 7 Ply</p> <p>5/8" 7 Ply</p> <p>3/4" 8 Ply</p> <ul style="list-style-type: none"> • Standard size 4' x 8' • Scarfed panels to 10'

Plum Creek Ultra-Pour O&ES Concrete Form

Specs	<ul style="list-style-type: none"> • Standard and premium grade available • All Group 1, Struc 1 species • Nox-Crete release agent • Highest quality edge seal
Standard Grade	<ul style="list-style-type: none"> • APA "B" grade Douglas Fir face and back • Face and back touch-sanded with 60-grit paper.
Premium Grade	<ul style="list-style-type: none"> • Superior "B" grade Douglas Fir face and back • Fully repaired panel • Face and back fully sanded with 60 grit paper
Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high-integrity Ultra-Core™ construction featuring composed cross bands for tight core gap tolerances more stringent than APA and industry specs • One piece "C" grade center
Construction & Thickness	<p>Thickness Ply count</p> <p>5/8" 7 Ply</p> <p>3/4" 7 Ply</p> <ul style="list-style-type: none"> • Standard size 4' x 8' • 2' x 8' size available • Full thickness • Oil and edge sealed

Plum Creek Ultra-Pour HDO Concrete Form, Edge Sealed

Specs	<ul style="list-style-type: none"> • Two step process • All Group 1, Struc 1 species • Highest quality edge seal 												
Faces	<ul style="list-style-type: none"> • APA "B" grade face • Smooth uniform finish enhances durability of product • Increased pours • Minimum grain transfer 												
Backs, Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high-integrity Ultra-Core™ construction featuring composed cross bands for tight core gap tolerances far more stringent than APA and industry specs • One piece "C" grade center and back 												
Construction & Thickness	<p>Thickness Ply count</p> <table data-bbox="592 821 1045 932"> <tr> <td>1/2"</td> <td>5 Ply</td> <td>120/30</td> <td>120/120</td> </tr> <tr> <td>5/8"</td> <td>7 Ply</td> <td>120/30</td> <td>120/120</td> </tr> <tr> <td>3/4"</td> <td>7 Ply</td> <td>120/30</td> <td>120/120</td> </tr> </table> <ul style="list-style-type: none"> • Standard size 4' x 8' • 2' x 8' available • Full thick 	1/2"	5 Ply	120/30	120/120	5/8"	7 Ply	120/30	120/120	3/4"	7 Ply	120/30	120/120
1/2"	5 Ply	120/30	120/120										
5/8"	7 Ply	120/30	120/120										
3/4"	7 Ply	120/30	120/120										

Plum Creek Ultra-Pour MDO Concrete Form, Oil and Edge Sealed

Specs	<ul style="list-style-type: none"> • One- and two-step process available • All Group 1, Struc 1 species • Nox-Crete release agent • Highest quality edge seal
One-Step Process	<ul style="list-style-type: none"> • APA "B" grade face • Paper and veneer are pressed together in a one step process • Minimum grain transfer • Matte finish
Two-Step Process	<ul style="list-style-type: none"> • APA "B" grade face • Paper is pressed to sanded blank in a secondary process • 2 side panels available • Minimum grain transfer • Matte finish
Centers & Cores	<ul style="list-style-type: none"> • Plum Creek's high-integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerances more stringent than APA and industry specs • One piece "C" grade center and back
Construction & Thickness	<p>Thickness Ply count</p> <p>1/2" 5 Ply</p> <p>5/8" 5 or 7 Ply</p> <p>3/4" 7 Ply</p> <ul style="list-style-type: none"> • Standard size 4' x 8' • 2' x 8' available • Full thickness • One or two side available